

## Lead Free Valves

### Series 8501L & 8502L

#### Brass Gate Valve

- Certified to NSF/ANSI 372 Lead Free
- 200 lb. CWP
- Full port (1/4 - 3)
- Screwed in bonnet
- Non-rising brass stem
- Cast brass
- Metal to metal bonnet/body seating surfaces
- ISO 9001:2008 manufacturer



| Size<br>in | Part Number |            | Packing |        | Weight<br>lb |
|------------|-------------|------------|---------|--------|--------------|
|            | Threaded    | Sweat      | Inner   | Master |              |
| 1/4        | 01718501CL  | -          | 12      | 72     | 0.6          |
| 3/8        | 01718501EL  | 01718502EL | 12      | 72     | 0.6          |
| 1/2        | 01718501GL  | 01718502GL | 12      | 72     | 0.6          |
| 3/4        | 01718501IL  | 01718502IL | 14      | 56     | 0.8          |
| 1          | 01718501KL  | 01718502KL | 5       | 40     | 1.2          |
| 1-1/4      | 01718501LL  | 01718502LL | 3       | 18     | 1.8          |
| 1-1/2      | 01718501ML  | 01718502ML | 6       | 24     | 2.2          |
| 2          | 01718501NL  | 01718502NL | 4       | 16     | 3.3          |
| 2-1/2      | 01718501PL  | 01718502PL | 1       | 6      | 6.4          |
| 3          | 01718501QL  | 01718502QL | 1       | 6      | 9.7          |
| 4          | 01718501TL  | -          | 1       | 4      | 17.0         |

### Series 8103L & 8104L

#### Brass Gate Valve with Drain

- Certified to NSF/ANSI 372 Lead Free
- 200 lb. CWP
- Full port
- Cast brass w/screwed in bonnet
- Solid wedge disc
- Non-rising stem
- Metal to metal bonnet/body seating surfaces
- ISO 9001:2008 manufacturer



| Size<br>in | Part Number |            | Packing |        | Weight<br>lb |
|------------|-------------|------------|---------|--------|--------------|
|            | Threaded    | Sweat      | Inner   | Master |              |
| 1/2        | 01718103GL  | 01718104GL | 12      | 72     | 0.72         |
| 3/4        | 01718103IL  | 01718104IL | 14      | 56     | 1.18         |
| 1          | 01718103KL  | 01718104KL | 8       | 32     | 1.26         |

### Series 8130L

#### Brass Gate Valve with Compression Ends

- Certified to NSF/ANSI 372 Lead Free
- 200 lb. CWP
- Full port, Cast brass
- Screwed in bonnet
- Non-rising stem
- ISO 9001:2008 manufacturer



| Size<br>in | Part Number      | Packing |        | Weight<br>lb |
|------------|------------------|---------|--------|--------------|
|            | Compression Ends | Inner   | Master |              |
| 1/2        | 01718130GL       | 10      | 60     | 0.8          |
| 3/4        | 01718130IL       | 10      | 40     | 1.0          |
| 1          | 01718130KL       | 8       | 32     | 1.4          |

### Brass In-Line Check Valve

- Certified to NSF/ANSI 372 Lead Free
- Rated at 200 psi
- Cast brass
- EPDM seat and seal - CV30L
- Viton seat & seal - CV35L
- Spring loaded, stainless steel spring, opens at 2 psi



| Size<br>in | Part Number |            | Packing |        | Weight<br>lb |
|------------|-------------|------------|---------|--------|--------------|
|            | Threaded    | Sweat      | Inner   | Master |              |
| 1/2        | 0209CV30GL  | 0209CV35GL | 10      | 150    | 0.4          |
| 3/4        | 0209CV30IL  | 0209CV35IL | 18      | 108    | 0.6          |
| 1          | 0209CV30KL  | 0209CV35KL | 10      | 60     | 0.9          |
| 1-1/4      | 0209CV30LL  | -          | 8       | 40     | 1.5          |
| 1-1/2      | 0209CV30ML  | -          | 5       | 30     | 1.5          |
| 2          | 0209CV30NL  | -          | 4       | 24     | 3.5          |

### Series 9191L & 9192L

#### Brass Swing Check Valve

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 372 Lead Free
- 200 lb. CWP
- Cast brass
- Forged brass disc
- ISO 9001:2008 manufacturer



| Size<br>in | Part Number |            | Packing |        | Weight<br>lb |
|------------|-------------|------------|---------|--------|--------------|
|            | Threaded    | Sweat      | Inner   | Master |              |
| 3/8        | 01739191EL  | -          | 25      | 150    | 0.5          |
| 1/2        | 01739191GL  | 01739192GL | 20      | 120    | 0.5          |
| 3/4        | 01739191IL  | 01739192IL | 12      | 72     | 0.6          |
| 1          | 01739191KL  | 01739192KL | 10      | 60     | 0.7          |
| 1-1/4      | 01739191LL  | 01739192LL | 8       | 32     | 1.5          |
| 1-1/2      | 01739191ML  | 01739192ML | 5       | 20     | 1.8          |
| 2          | 01739191NL  | 01739192NL | 4       | 16     | 3            |
| 2-1/2      | 01739191PL  | 01739192PL | 1       | 8      | 5.6          |
| 3          | 01739191QL  | 01739192QL | 1       | 8      | 7.2          |
| 4          | 01739191TL  | -          | 1       | 8      | 11.4         |

### Series 7200L

#### Ground Key Stop & Drain

- Certified to SWDA and California AB1953
- Max 150 psi @ 100°F



| Size<br>in | Part Number | Packing |        | Weight<br>lb |
|------------|-------------|---------|--------|--------------|
|            | Threaded    | Inner   | Master |              |
| 1/2        | 01767200GL  | 6       | 48     | .9           |
| 3/4        | 01767200IL  | 6       | 48     | 1.0          |
| 1          | 01767200KL  | 4       | 32     | 2.0          |